

Series / Serie / Série


TC	TB	TE	TJ	TF	TF Clutch	DF
----	----	----	----	----	--------------	----

Page / Seite / Côte / Lado

Technical Information / Technische Information	6...7	20...21	38...39	74...75	90...91	124	128
Segni / Caractéristique							
Performance Data / Leistungsdaten	8...12	22...26	40...44	76...80	92...95	92...95	92...95
Puissance / Potenza							
Side Load Information / Radiale Wellenbelastung ...	13	27	46...47	81	96	96	129
Charges Radiale / Carico Radia							
Mounting / Gehäuse	14	28...29	48...51	82	97...101	125	130
Carter / Scatola							
Ports / Anschlüsse	15	30...31	52...54	83	102...105	125	130
Orifices / Connessione							
Shafts / Abtriebswellen	16...17	32...35	55...63	84	106...121	126	131
Arbre / Eje Salida							
Ordering Information / Bestellschlüssel	18	36	64	85	122...123	127	132...133
System de Commande / Systeme di Ordinazione							
Accessories / Zubehör / Accessoires / Accesorios							
Cross- Over Relief Valve / Schockvent`il	68...69	68...69	68...69	N/A	213	N/A	N/A
Valve Anti Choc / Valvola di Soprapressione							
Speed Sensor / Drehzahlsensor	N/A	N/A	65...66	N/A	210...211	N/A	N/A
Compte Tours / Contagiri							
Hot Oil Shuttle Valve / Spülventil	N/A	67	67	86	212	N/A	N/A
Valve De Rincage / Valvola Scambiatrice							
Internal Releif Valve / Schockventil intern	N/A	70	70	N/A	214	N/A	N/A
Soupape de sécurité interne / Regolatrice di pressione interna							
Multiple Disc Brake / Lamellenbremse	N/A	71	71	N/A	215...217	N/A	N/A
Frein Multi-Disque / Freno multidisco							

EU Euro Standards
Standard product offerings in Europe, Middle East and Africa. For NA Standards consult the factory for leadtime and pricing.

US US Standards
Standard product offerings available in all parts of the world except Europe, Middle East and Africa. For EU Standards consult the factory for leadtime and pricing.



Series / Serie / Série

TG | BG | DG | TH | BH

Page / Seite / Côte / Lado

Technical Information / Technische Information Segni / Caractéristique	134...135	170	180	186...187	204
Performance Data / Leistungsdaten Puissance / Potenza	136...140	136...140	136...140	188...191	188...191
Side Load Information / Radiale Wellenbelastung ... Charges Radiale / Carico Radiale	141	171	181	192	205
Mounting / Gehäuse Carter / Scatola	143...147	172...173	182	193...194	206
Ports / Anschlüsse Orifices / Connessione	148...151	174...175	182	196...199	207
Shafts / Abtriebswellen Arbre / Eje Salida	152...167	176...177	183	200...201	208
Ordering Information / Bestellschlüssel System de Commande / Systeme di Ordinazione	168..169	178	184...185	202...203	209
Accessories/Zubehör/Accessoires/Accesorios					
Cross- Over Relief Valve / Schockvent`il Valve Anti Choc / Valvola di Soprapressione	213	N/A	N/A	213	N/A
Speed Sensor / Drehzahlsensor Compte Tours / Contagiri	210...211	N/A	N/A	N/A	N/A
Hot Oil Shuttle Valve / Spülventil Valve De Rincage / Valvola Scambiatrice	212	N/A	N/A	212	N/A
Internal Releif Valve / Schockventil intern Soupape de sécurité interne / Regolatrice di pressione interna	214	N/A	N/A	214	N/A
Multiple Disc Brake / Lamellenbremse Frein Multi-Disque / Freno multidisco	215...217	N/A	N/A	N/A	N/A

EU Euro Standards
Standard product offerings in Europe, Middle East and Africa. For NA Standards consult the factory for leadtime and pricing.

US US Standards
Standard product offerings available in all parts of the world except Europe, Middle East and Africa. For EU Standards consult the factory for leadtime and pricing.

Table of Contents

High Speed Hydraulic Motor

Introduction C226 - C227

M4 Series C228 - C229

M2 Series C230 - C233

Ordering Information C235

C

Output Performance / Leistungabgabe
Puissance de Sortie / Potenza Meccanica

TC	TB	TE	TJ	TF	TG	TH
KW (HP)	KW (HP)	KW (HP)	KW (HP)	KW (HP)	KW (HP)	KW (HP)
7.5 (10)	13 (18)	14 (19)	14 (19)	24 (32)	33 (44)	33 (44)




Side Load / Radiale Wellenlast
 Charges Radiale / Carico Radiale



Torque / Drehmoment
 Couple / Coppia



Speed / Drehzahl
 Vitesse de Rotation / Velocità di Rotazione



int. =
 Intermittent operation rating applies to 10% of every minute.
 Intermittierende Werte maximal: 10% von jeder Betriebsminute.

int. =
 Fonctionnement intermitt.: 10% max de chaque minute d'utilisation.
 Capacidad de funcionamiento intermitente valida para 10% por cada minuto.



Low Speed, High Torque Hydraulic Motors

Catalog No. HY13-1510-001/NA,EU

